

LED CAMERA RING LIGHT

Executive Standard: GB 7000.1-2015 GB 7000.204-2008

P01



FC (E & & X & X & X



SHENZHEN DISCOVER TECHNOLOGY Co., LTD

Add: 4F, 4B, Haomai High-tech Park 387 Huating Rd. Dalang St.

Longhua District, Shenzhen 518109 China.

Berlin St. 74: 400-6618-101 Web; www.luxceo.com

P01



Thanks for choosing our product, please read this instruction manual carefully before using and operate it according to the instructions

Product Features

- 1. Stepless brightness and color temperature. The brightest level is up to 800LM
- 2. Built-in rechargeable 5000mAh lithium battery. It can continuously work up to 2.5 hours at the brightest level.
- 3. With 1/4" thread and Hot Shoe mount on the bottom. It can be mounted on tripod and camera.
- 4. Great for photography, video shooting and live broadcasting,
- 5. It can also work while charging, (via 5V 2A adpater)
- 6. 240pcs high CRI>95 LED.


What's included in the box

LED Ring Light x1 Diffuser x1 User Manual x1

USB Cable x1 Certificate x1

-- 01

Product Appearance



- A Light Cover
- **B** Hot Shoe Mount
- ON-OFF Switch/Brightness Control Switch
- Power/Charging indicator
- Color Temperature control switch
- Diffuser (It can attach to light when used)
- @ 1/4" standard nut on the bottom
- Micro USB Charging port

-02

Charging Time

It will take about 7 hours to get full charge by 2A adaptor. (It will take about 12 hours to get full charge by 1A adaptor.)

Power Display



Power Indicator Status in Charging

Battery C (%)	LED1	LED2	LED3	LED4
Full Charge	ON	ON	ON	ON
75%≤C	ON	ON	ON	Flash
50%≤C<75%	ON	ON	Flash	OFF
25%≤C<50%	ON	Flash	OFF	OFF
C<25%	Flash	OFF	OFF	OFF

When the product is working in low battery, the first indicator will flash.

Power Indicator Status in Working

电量C(%)	LED1	LED2	LED3	LED4
C≥75%	ON	ON	ON	ON
50%≤C<75%	ON	ON	ON	OFF
25%≤C<50%	ON	ON	OFF	OFF
3%≤C<25%	ON	OFF	OFF	OFF
0%≤C<3%	Flash	OFF	OFF	OFF

Specifications

Name	LED Camera Ring Light			
Model	P01		Power	7W(max)
Input	DC5V/2A		CRI	Ra≥95
Brightness	800lm(max)		Weight	260g
CCT	3000K - 6000K			
Size	~178×140×34mm			
Battery	Li-ion 3.7V / 5000mAh / 18.5Wh			
Charging Time	~3 hours(with 2A adapter)			
Operating temp	erature	0~40°C		
Storage temperature -10~50°C		2		

Note: LED light source of this lamp is irreplaceable, please replace the whole lamp when LED Light source comes to the end of life.



In the following situations, immediately cut off the power supply and seek help from a technician.

- O Any liquid, including rain or water, spills into the product that will damage electronic components.
- O Product gives off gas or have an unusual flickering.
- O The cable is damage and one can see the bare wire.
- The shell is broken.

PLEASE NOTE

- 1. Keep the batteries away from fires and high temperatures.
- 2. Do not place the light in fire in case of explosion.
- 3. Do not modify or take this product apart. Don't shake, heat or strike it
- 4. Please check the voltage requirements before using to avoid damage to the light.
- 5. Children should use this product in the company of their guardians. To avoid eye injury, please do not look directly at the glowing surface.
- 6. Please charge the light at least once every three months. And don't put it into water or wet environment while charging
- 7. Please plug out the power cord while not using this light to avoid injury and damage
- 8. Please do not put it in damp environment or water when charging







Customer Information

Spin Button Instruction

Working Time Instruction

2. It can also work when charging.

Use a soft, dry cloth to wipe the surface

General Maintenance

1. The spin clockwise of brightness spin button is 0% - 100% and spin anticlockwise is 100%-0%. When you hear the sound of "ka"

in spin clockwise, it means you turn on the light. When you hear

the sound of "ka" in spin anticlockwise, it means you turn off the

1. It can continuously work up to 2.5 hours at the brightest level.

Do not use liquids or solvents as this may damage the surface.

2. The spin clockwise of color temperature spin button is 3000K-6000K and spin anticlockwise is 6000K-3000K.

Attn:	 Tel:	

Product Information

Product Model: Purchase Date: Product Serial Number:

Product Maintenance Record

Date	Maintenance Center Name	Fault and Handling	Finish Date

The Dealer Information

Company Name:

Add:	
Signature:	

Purshase Date:

The user to save Lost not fill

V1.0

-05